

HEALTH HAZARDS (ACUTE AND CHRONIC):

Avoid long term and repeated contact.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Not applicable.

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: If swallowed, do not induce vomiting. EYES: In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes. SKIN: In case of skin contact, remove promptly by wiping, followed by waterless hand cleaner and soap and water. INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other supportive measures as required. Get medical attention.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sawdust, vermiculite, or other absorbent material and place into containers for disposal.

WASTE DISPOSAL METHOD:

Waste material must be disposed of in accordance with Federal, State, and Local environmental control regulations. Empty containers should be recycled or disposed of through an approved Waste Management Facility.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 120 deg. F. Store large quantities in buildings designed and protected for storage of NFPA Flammable liquids.

OTHER PRECAUTIONS:

If this material is part of a multiple component coating system, read the MSDS for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches. Containers of this material may be hazardous when emptied since they retain residues. Do not cut, puncture, or weld on or near container.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION:

Overexposure to vapors may be prevented by ensuring ventilation controls, vapor exhaust or fresh air entry. If TLV of any component is exceeded, use an appropriate NIOSH/MSHA approved respirator. Follow respirator manufacturers directions for respirator use.

VENTILATION:

Provide sufficient mechanical and/or local exhaust ventilation to keep the concentration of ingredients listed in Section II below the lowest exposure limits.

PROTECTIVE GLOVES:

Impermeable chemical handling gloves for skin protection.

EYE PROTECTION:

Use chemical safety glasses, goggles, and faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended. Clean or discard contaminated clothing and shoes.

WORK/HYGIENIC PRACTICES:

Eye washes and safety showers in the workplace are recommended.

===== SECTION IX - TRANSPORTATION INFORMATION =====

PROPER SHIPPING NAME	HAZARD CLASS	UN NUMBER	PACKING GROUP
CONSUMER COMMODITY	ORM-D	DOES NOT APPLY	DOES NOT APPLY

===== SECTION X - DISCLAIMER =====

The information and recommendations contained herein are believed to be accurate at the time of preparation or obtained from sources believed to be generally reliable. Fasse Paint Co. will not be held liable for claims relating to any party's use of or reliance on information contained herein, regardless of whether it is claimed the information is inaccurate.