

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY**SPECIALTY
LACQUER SPRAYS****DESCRIPTION AND USES**

Rust-Oleum® Lacquer Sprays is a high luster coating that provides a smooth, durable, ultra-hard, gloss finish on wood, metal, and more. Lacquer sprays are ideal for furniture, lamps, picture frames, and more.

PRODUCTS**FINISHES**

1904830	Gloss White
1905830	Gloss Black
1906830	Gloss Clear
243826	Chinese Red

PRODUCT APPLICATION**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. LEAD IS TOXIC. Contact the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 30 minutes and fully dry in 24 hours. Recoat at any time.

CLEAN-UP

When finished spraying, clear spray valve by turning can upside down and depressing spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

PHYSICAL PROPERTIES

		LACQUER SPRAYS
Resin Type		Acrylic Lacquer
Pigment Type		Proprietary
MIR		1.4 Max
Fill Weight		12 oz.
Solvents		Toluene and Xylene
Recommended Dry Film Thickness (DFT) per coat		1.0-2.0 mils
Practical Coverage at Recommended DFT (assumes 15% material loss)		7 sq. ft./can (0.63 m ² /can)
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	20 minutes
	Fully Dry	30 minutes
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Safety Information	Flash Point	-156°F (-144°C)
	Contains	Lead-free
	Warning!	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.