

# Material Safety Data Sheet

## SECTION 1

## CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PUNCHEASY

MOTOR OIL, INC.  
1490 JARVIS AVENUE  
ELK GROVE VILLAGE, IL 60007  
Phone (847) 956-7550 Fax (847) 956-0399

CAS Registry Number  
Chemical Family  
Product Type  
Preparation/Revision Date

Not applicable for mixtures  
Petroleum hydrocarbon  
Heavy Duty Chlorinated Drawing and Stamping Oil  
08/2009

## SECTION 2

## COMPOSITION / INFORMATION ON INGREDIENTS

Component Name	CAS Number	OSHA PEL	ACGIH TLV	% (Optional)
Chlorinated Paraffin	Trade Secret	NE	NE	
Severely Hydro-treated Base Oil	64742-52-5	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	

## SECTION 3

## HAZARDS IDENTIFICATION

Principal Hazard(s)	Contains petroleum oil. Contains chlorinated paraffin. Avoid breathing mists or vapors. Avoid prolonged or repeated skin contact.
---------------------	---

## SECTION 4

## FIRST AID MEASURES

Oral	DO NOT induce vomiting. Get immediate medical attention
Eye	Flush eye(s) with water for at least 15 minutes or until irritation subsides. Get medical attention if eye irritation develops or persists
Skin	Wash with soap and water. Immediately remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before re-use. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.
Inhalation	Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If adverse effects are observed, remove exposed person to fresh air. If breathing is labored, administer oxygen. If breathing has stopped, apply artificial respiration. If overexposed to oil mist, remove from further exposure until excessive oil mist subsides.

**SECTION 5 FIRE FIGHTING MEASURES**

Flash Point	350 °F COC Minimum
Upper Flammable Limit	Not Determined
Lower Flammable Limit	Not Determined
Extinguishing Media	Carbon Dioxide, dry chemical, water spray (fog) and foam. Note: water, water fog and foam may cause frothing and spattering.
Special Fire fighting Procedures	Wear self-contained breathing apparatus. Avoid breathing fumes and vapors. Use water spray (fog) to cool containers exposed to high heat or open flames,
Unusual Fire and Explosion Hazards	Empty containers contain residue and/or vapors. DO NOT WELD, CUT, PRESSURIZE, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, SPARKS, FLAME, STATIC ELECTRICITY OR OTHER SUCH SOURCES OF IGNITION. Keep empty containers closed and dispose of in an environmentally safe manner and in accordance with all government regulations.
Auto-ignition Temperature	Not Determined

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

Spill Procedures	Evacuate all non-essential personal. Personal Protective Equipment must be worn (see Personal Protection Section for PPE recommendations). Remove sources of ignition. Ventilate spill area. Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Assure conformity with applicable Federal, state and local regulations.
------------------	---

**SECTION 7 HANDLING AND STORAGE**

Handling Procedures	Keep away from potential sources of ignition. Avoid breathing vapors if present. Keep containers closed when not in use. Wash thoroughly after handling. Make sure that proper warning labels are affixed in accordance with 29 CFR 1910.1200. Use good personal hygiene around product. Do not smoke or eat around product.
Storage Procedures	Do not store near potential sources of ignition. Store in a well ventilated area. Store in a dry area. Do not store around food or eating areas. Avoid storing above 120 °F for prolonged periods of time.

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

Ventilation Procedures	Use material in well ventilated areas only. Additional ventilation or exhaust may be required to maintain air concentrations below recommended exposure limits.
Glove Protection	Use chemical resistant gloves, if needed, to avoid prolonged or repeated skin contact.
Eye Protection	Safety glasses recommended. Use splash goggles or face shield when eye contact may occur.
Respiratory Protection	Under normal conditions, respirator is not usually required. Use NIOSH/MSHA approved disposable dust/mist mask if the recommended exposure limit is exceeded.
Clothing Recommendation	Use a chemical resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

**SECTION 9****PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Amber colored liquid	Vapor Pressure	Not Determined
Specific Gravity	1.2-1.3	Vapor Density (Air = 1)	Greater than 5
Viscosity	Approx. 150 cSt @ 40 °C	Evaporation Rate	Not Determined
Odor	Bland	Pour or Melting Point	20 °F
pH	Essentially neutral	Boiling Point	Not Determined
Odor Threshold	Not Determined	Percent Volatile	None
Water Solubility	Negligible	Molecular Weight	Not Determined

**SECTION 10****STABILITY AND REACTIVITY**

Stability	Material is normally stable at room temperature and pressure. See the <b>Handling and Storage Section</b> for further details.
Incompatibility	Strong oxidizing agents.
Hazardous Polymerization	Will not occur.
Thermal Decomposition	Carbon monoxide and/or carbon dioxide. Hydrogen Chloride gas will also form.

**SECTION 11****TOXICOLOGICAL INFORMATION**

Oral Toxicity	Not Determined.
Eye Irritation	Product contacting eyes may cause eye irritation.
Skin Irritation	May cause skin irritation. Prolonged or repeated contact may cause dermatitis. Symptoms may include redness, edema, drying, defatting and cracking of skin.
Dermal Toxicity	Not Determined.
Inhalation Toxicity	Not Determined.
Respiratory Irritation	If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.
Dermal Sensitivity	No data available to indicate product or components may be skin sensitizer.
Inhalation Sensitivity	No data given to indicate product or components may be respiratory sensitizer.
Chronic Toxicity	Not Determined.
Carcinogenicity	The components of this product has not been found to be a carcinogen under either NTP, IARC Monographs or current OSHA regulations.
Other	Under conditions which may generate mists, observe the OSHA PEL 5 mg/m <sup>3</sup> .

**SECTION 12****ECOLOGICAL INFORMATION**

No Data Given.

**SECTION 13****SHIPPING CONSIDERATIONS**

U. S. DOT Shipping Name	Not regulated by DOT
Hazard Class	Not applicable
DOT Identification Number	Not applicable
DOT Shipping Label	Not regulated by DOT

**SECTION 14****DISPOSAL INFORMATION**

Dispose of following all Federal, state and local regulations. After use, it is the responsibility of the user to determine the disposal status of the spend fluid.

**SECTION 15****REGULATORY INFORMATION**

U. S. TSCA Inventory	All components of this product are listed on the TSCA Inventory.				
SARA 302 Threshold Planning Quantity	No RQ for product or any constituent greater than 1.0% or 0.1% (carcinogen).				
SARA 304 Reportable Qty	No RQ for product or any constituent greater than 1.0% or 0.1% (carcinogen).				
SARA 311 Categories	<b>EPA Hazard Classification Code</b>				
	Acute	Chronic	Fire	Pressure	Reactivity
	Yes	NA	No	NA	NA
SARA 313 Supplier Notification	Chlorinated Alkanes C10-13 1 to 5% CAS# NA				
CERCLA Hazardous Substances	No chemicals in this product are subject to the reporting requirements of CERCLA.				
Clean Water Act	Under Section 311(b)(4) of this act, contamination of surface waters by petroleum products must be reported immediately to the National Response Center.				

**CALIFORNIA PROP 65.**

Puncheasy does not contain any components listed under California Proposition 65.

**SECTION 16****OTHER INFORMATION****HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)****HEALTH = 1 FIRE = 1 REACTIVITY = 0 PP = B****Rating: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Extreme**

Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, **MOTOR OIL, INC.** makes no representations as to the completeness or accuracy thereof. **MOTOR OIL, INC.** makes no warranty whatsoever, expressed or implied, of **MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE** since the conditions of use are beyond our control. **MOTOR OIL, INC.** assumes no responsibility for injury to recipient or to third persons for any damage to any property and recipient.